

GLASS DOOR

GABINETS DISPLAY

By **itc**

Classical and Stylish Cabinet Display



EURO-2DR



EURO-3DR



EURO-CAKE



EURO-4DR-ICE

ITC's Glass Door Cabinets Display is available in 4 classical and stylish models: EURO-2DR, EURO-3DR, EURO-CAKE and EURO-2DR-ICE. It is widely used in food storage such as beverages and cakes. This countertop display refrigerator utilizes an efficient 1/2, and 3/8 horse power with R-134a/R22 refrigerant to maintain a cooling performance of 2-6/-10, 2-6 and 4°C - 8°C. The fully insulated glass doors can largely promote and speed the cooling process up. Moreover, we trim the doors with durable stainless steel to ensure the high durability of the cabinet except for the EURO-CAKE model. This model already has double vacuum layers glass, which can perform as excellence insulation and can prevent fog from forming. The cooler also features interior lights and door lock for security.

I.T.C. (1993) CO., LTD.

10, 12 ซอยรามคำแหง 118 แยก 61 แขวงสะพานสูง เขตสะพานสูง กทม. 10240
10, 12 Soi Ramkhamhaeng 118 Yak 61, Saphansoong, Saphansoong, Bangkok 10240 Thailand.

Tel : +66-2184-0055 Fax : +66-2184-0065

www.itc-group.co.th info@itc-group.co.th



GLASS DOOR

GABINETS DISPLAY

By **itc**



EURO-4DR-ICE



EURO-2DR



EURO-3DR



EURO-CAKE

DESCRIPTION		MODEL / รุ่น			
		EURO-4 DR-ICE	EURO-2DR	EURO-3DR	EURO-CAKE
Cabinet (ตู้)	External Dimension (mm) (ขนาดภายนอก) (W x D x H)	1,150 x 750 x 2,090	1,150 x 750 x 2,090	1,740 x 750 x 2,090	1,500 x 790 x 1,410
	Insulation (ฉนวนห้องเย็น)	Polyurethane Foam (โพลียูเรเทนโฟม)			
	Glass Door (บานประตู)	Insulated Panel Glass Door Condenser Stop (กระจกสูทากาศ 2 ชั้น ป้องกันการเกิดฝ้า)			Curve Glass Door (กระจกโค้ง)
	Colour (สี)	White / ขาว	White / ขาว	White / ขาว	White / ขาว
	Shelves (ชั้นวางสินค้า) (PCS)	4	5	5	4
	Internal Lighting (แสงสว่างภายในตู้) (Watts)	1 x 36 W	1 x 36 W	2 x 36 W	5 x 36 W
Refrigeration (เครื่องทำความเย็น)	Compressor (คอมเพรสเซอร์) (HP)	1/2	3/8	1/2	1/2
	Cooling Performance (ความเย็น) (°C)	2-6/-10	2-6	2-6	4-8
	Refrigerant (น้ำยาทำความเย็น)	R134a / R-22 (On Request)			
	Defrost System (ระบบละลายน้ำแข็ง)	No Frost (ไม่มีน้ำแข็งเกาะ)			
General Features (ทั่วไป)	Current (การใช้กระแสไฟฟ้า) (Amp)	4.2	3.2	4.2	4.2
	Power Supply (กำลังไฟฟ้า)	220V / 1Ph/50Hz	220V / 1Ph/50Hz	220V / 1Ph/50Hz	220V / 1Ph/50Hz
	Net Weight (น้ำหนักสุทธิ) (Kg)	100	110	190	95

** SPECIFICATIONS ARE SUBJECTED TO CHANGE WITHOUT NOTICE.

คุณลักษณะตามรายละเอียดที่ระบุไว้ สามารถเปลี่ยนแปลงได้ตามต้องการ