

Glycol

Unit Cooler By **itc**

**Stainless Steel
Fan Blade and Guard**



Stainless Steel Casing and Fan Blade



I.T.C. (1993) CO., LTD.


10, 12 ซอยรามคำแหง 118 แยก 61 แขวงสะพานสูง เขตสะพานสูง กทม. 10240
10, 12 Soi Ramkhamhaeng 118 Yak 61, Saphansong, Saphansong, Bangkok 10240 Thailand.

Tel : +66-2184-0055 Fax : +66-2184-0065

www.itc-group.co.th

info@itc-group.co.th





Specifications

MODEL	fin pitch mm	Qo kW	Air Vol m ³ /h	Air Throw m	No. of fan	Fan Motor @w	PPG flow m ³ /h	P Drop bar	Dimension				Weight kg
									L mm	W mm	H mm	E mm	
150-ISG-241	4	15.4	6,300	18	1	400	2.8	0.5	1510	710	950	1000	85
250-ISG-241	4	23.2	12,600	18	2	400	4.2	0.3	2510	710	950	2000	147
350-ISG-241	4	52.3	18,900	18	3	400	9.5	0.8	3510	710	950	1000	377
150-ISG-341	4	26.3	6,000	18	1	400	4.8	0.6	1510	810	950	1000	94
250-ISG-341	4	50.8	12,000	18	2	400	9.2	0.5	2510	810	950	2000	162
350-ISG-341	4	86.5	18,000	18	3	400	15.8	0.8	3510	810	950	1000	415
150-ISG-271	7	8.5	6,500	18.5	1	400	1.6	0.3	1510	710	950	1000	77
250-ISG-271	7	22.7	13,000	18.5	2	400	4.1	0.8	2510	710	950	2000	132
350-ISG-271	7	34.6	19,500	18.5	3	400	6.3	0.7	3510	710	950	1000	339
150-ISG-371	7	16.5	6,350	18.5	1	400	3.0	0.6	1510	810	950	1000	84
250-ISG-371	7	32.5	12,700	18.5	2	400	5.9	0.5	2510	810	950	2000	146
350-ISG-371	7	58.4	19,050	18.5	3	400	10.6	0.9	3510	810	950	1000	373

Single Discharge Draw thru Fan; Copper Tube /Coated Aluminum Fin
 Room temp = 10°C; 70%RH; PPG 27% -3/+2°C;

Standard Specification

- Copper Tube / Coated Aluminum Fin
- Tube arrangement Square 50 x 50 mm
- Casing Stainless Steel 304
- Double Tray with Insulation
- **Stainless Steel Fan Blade**
- **Aluminum Housing Fan Motor**
- Motor speed 1300 rpm
- Power 380V/3ph/50hz
- Ceiling Mount
- Air Defrost

Option

- Electric Defrost
- Droplet Separator
- Long Air Throw Nozzle
- Connection for Air Sock
- Hinged Drip Tray
- Hinged Fan Plate

